


Datasheet Series SE

Model	SE3PH16SE-CBFI-DC24 (SE-3PH-6x1PH-DC24)		
Order no.	20-009-000-01		
Mains supply	3/N/PE AC 400/230 V 50 Hz		
Power distribution	max. 3,6 kVA (1~) / max. 10,8 kVA (3~)		
Connection	16 A		
Phase indicator	yes		
Central power-off	yes		
Fuse (control circuit)	2 A T		
Residual current circuit breaker	30 mA		
Circuit breaker	3x 16 A Type C (1~) 2x 16 A Type C (3~)		
Connections deactivatable	-		
Connections permanent	7x L/N/PE (multiple sockets)		
Weight ca.			
Low voltage source	24 V, 8 A		
Housing ¹⁾	19" - 3 U		

1. 1 U = 44.45 mm

Control circuit	
Fuse	T2A
Operating conditions	
Operating temperature	5 ... 40 °C
Stock temperature	-25 ... 65 °C
Max. operating height	2,000 m above sea level
Pollution degree	2
Max. humidity	80 % at 31 °C, linear decreasing to 50 % at 40 °C
Weight	see model overview
Mains	see model overview
Mains voltage tolerance	-15 ... 10 %
Housing	
Dimensions, weight	see model overview
Color	Front panel RAL7035 (light grey) Rear panel stainless steel (except SE1PH16S-FP-TB, SE3PH16S-FP-TB, SE3PH32S-FP-TB) Side, top zinc grey (except SE1PH16S-FP-TB, SE3PH16S-FP-TB, SE3PH32S-FP-TB)
Safety and EMC	
Protection class	1
Electrical safety	DIN EN 61010-1
EMC	DIN EN 61326-1 DIN EN 55011 DIN EN 61000-3-2 DIN EN 61000-3-3
Warranty	2 years